Clamp Multimeter

VICTOR®

606+

606A+

606B+

606C+

FUNCTION	606+	606A+	606B+	606C+	Accuracy
DCV	200mV/2V/20V	600mV/6V/60V	600mV/6V/60V	600mV/6V/60V	± (0.5%+7)
	200V	600V	600V	600V	± (1.0%+ 20)
	600V	/	/	/	± (1.2%+ 20)
ACV	2V/20V	6V/60V	6V/60V	6V/60V	± (0.8%+ 10)
	200V	600V	600V	600V	± (1.2%+ 25)
	600V	/	/	/	± (1.5%+25)
LOW INPEDANCE ACV	2V/20V	6V/60V	6V/60V	6V/60V	± (0.8%+ 10)
	200V	300V	300V	/	± (1.2%+25)
	300V	/	/	/	± (1.5%+ 25)
	/	/	/	300V	± (1.0%+12)
ACA	2A	6A	6A	/	± (4.0%+ 50)
	20A	60A	60A	/	± (4.0%+ 35)
	200A/600A	600A	600A	/	± (4.0%+15)
	/	/	/	60A/600A	± (4.0%+10)
DCA	/	/	/	60A/600A	± (4.0%+10)
RESISTENCE	200Ω/2kΩ/20kΩ /200kΩ/2MΩ	600Ω/6kΩ/60kΩ /600kΩ/6MΩ	600Ω/6kΩ/60kΩ /600kΩ/6MΩ	600Ω/6kΩ/60kΩ /600kΩ/6MΩ	± (1.0%+ 5)
	20MΩ	20MΩ	20MΩ	20MΩ	± (1.5%+15)
	/	60MΩ	60MΩ	60MΩ	± (2.5%+20)
CAPACITANCE	/	6nF	6nF	6nF	± (5.0%+40)
	/	60nF/600nF/6uF	60nF/600nF/6uF	60nF/600nF/6uF	± (5.0%+ 10)
	/	60uF/600uF/6mF	60uF/600uF/6mF	60uF/600uF/6mF	
FREQUENCY	/	10Hz/100Hz/1kHz/ 10kHz/100kHz/ 1MHz/10MHz	10Hz/100Hz/1kHz/ 10kHz/100kHz/ 1MHz/10MHz	10Hz/100Hz/1kHz /10kHz/100kHz/ 1MHz/10MHz	± (0.3%+3)
TEMPERATURE	/	/	-20℃~1000℃ (-4-1832)°F	-20℃~1000℃ (-4-1832)°F	/

Display method	LCD display 5999 count	Max/Min	√
Maximum display	5999 count (606+ 1999count)	Low Z	√
Diode measurement	√	Working temperature and humidity	(0- 40) ℃ <75%
Data retention	√	Storage temperature and humidity	(-10~50)℃<80%
NCV measurement	√	Automatic shut-down	About 15 minutes
Fire detection	√	Over-range display	the highest digit displays OL
Low voltage warning	√	Unit symbol	√
Flashlight lighting	√	Open jaws	35mm
True effective value	√	input resistance	10MΩ
INRUSH	606C+ only	Sampling rate	3 times/sec
VFC	606C+ only	power supply	Two AAA batteries

EMC
LVD CE

فروشگاه آذرپرتو
www.azarparto.com